

# AFCONA - 3037



## Chemical Composition

Blend of high-boiling point aromatic-free petroleum solvent, ketone and ether solvents, including a highly compatible polysiloxane.

## Product general description

Designed as anti-blushing agent for thermoplastic systems, an anti solvent- popping agent for all baking paints, and acts as flow agent for solvent-based paints.

## Product Properties

AFCONA – 3037 is a combination of high boiling point solvents. It also contains some amount of highly compatible polyether modified polysiloxane, which further promotes the leveling properties of paints.

Due to its low evaporating property as well as a well balance of solvency power, AFCONA – 3037 is very suitable to use as anti-blushing for thermoplastic system like NC and TPA.

AFCONA – 3037 also can prevent streaking during painting and spraying of chlorinated rubber and coatings based on other chlorinated polymers.

In baking paints, solvent boiling and solvent popping are common problems. Addition of AFCONA – 3037 to the system will prevent this problem to happen.

AFCONA – 3037 also act as a good flow agent for all solvent-based systems. In addition, the presence of polysiloxane in AFCONA – 3037 will further improve the levelling and anti-crater properties of the paint system. The well balanced combination of solvency power of AFCONA – 3037 makes it compatible with almost all solvent based system.

## Product Specification

|                      |   |
|----------------------|---|
| Density              | 0.77 – 0.81 g/cm <sup>3</sup> (20°C)                |
| The refractive index | 1.420 – 1.435 (25°C)                                |
| Flash point          | 45°C  |
| Appearance           | Clear to slightly hazy/<br>colourless liquid (25°C) |

## Addition and dosage

3 - 5% on total formulation.

## Incorporation

AFCONA-3037 can be added in any stage of production process. It also can be added on sites where minimal stirring on hand for incorporating this product into the system.

## Storage

AFCONA-3037 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

## Packaging

20kg and 160kg non-returnable containers

AFCONA ADDITIVES

Web Site : [www.afcona.com](http://www.afcona.com)

This information and all further technical advice are based on our present knowledge and experience. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used. We reserve the right to make any changes according to science and technological progress or further developments.

This version replaces all previous ones.