

AFCONA - 3233



Chemical Composition

Organic modified polyether polysiloxane.

Product general description

Additive designed as slip and leveling for solvent based and water born coatings.

Product Properties:

AFCONA-3233 is mainly used as general slip and leveling agent for all solvent-based coatings to prevent Bénard Cells, provide leveling and works as anti-crater agent. The slip performance is not so high comparing to AFCONA – 3031, AFCONA – 3033 and AFCONA – 3230. Thus, this is a moderate slip leveling agent but the slip characteristic is dry type.

AFCONA-3233 can be used as leveling and anti-crater agent in water as well as in solvent-based applications. This product will stabilize more foam in water-based coatings.

The special properties and recommended systems for AFCONA – 3233 are:

- 1) A very economic and effective slip and leveling agent for air-drying alkyd systems.
- 2) A very effective anti-crater agent for polyurethane systems. It also gives very less inner bubble sensitivity in polyurethane system.
- 3) Perform as a superior additive against Bénard Cells in all solvent-based systems.
- 4) Suitable for industrial baking systems, where baking temperature is less than 170°.
- 5) Can be added into the grinding phase to speed up the wetting and grinding speed of pigments.
- 6) Due to the foam stabilizing behavior not suitable for foam sensitive systems like solvent-free epoxy floor coatings.
- 7) Basically AFCONA – 3233 can be used in almost all solvent-based coatings as slip and leveling agent.

Product Specification

Non-volatile matter	≥ 96 % (120°C,0.5h)
The refractive index	1.440 – 1.450 (25°C)
Flash point	> 100°C
Appearance	Clear to slightly hazy/ yellowish liquid (25°C)

Addition and dosage

0.05 – 1.0% on total formulation. In general under normal conditions, the dosage is 0.10 – 0.50% based on total formulation.

Incorporation

AFCONA-3233 can be added at any stage during the production process.

Storage

AFCONA-3233 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

Packaging

30kg and 200kg non-returnable containers

AFCONA ADDITIVES

Web Site : www.afcona.com

This information and all further technical advice are based on our present knowledge and experience. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used. We reserve the right to make any changes according to science and technological progress or further developments.

This version replaces all previous ones.